



# ***THERMOSTATIC WATER BATH MLW-B16***

# Thermostatic Water Bath MLW-B16

## Features:

- \* Stainless steel inner chamber and upper cover.
- \* Adopt new design structure, which could avoid the leakage of steam.
- \* PID Mircoprocessor controller, LED display.

## Technical Parameters:

<b>Model no.</b>	<b>MLW-B16</b>
Capacity	18L
Temp. Range	RT.-100°C
Temp. Fluctuation	±0.5°C
Temp. Accuracy	≤±1°C
Time Range	0~999min
Power	1500W
Voltage	AC110/220VV±10%, 50/60Hz
Internal Size(mm)	470*300*130
External Size(mm)	500*340*220
Packing Size(mm)	600*400*280
Net Weight(kg)	9
Gross Weight(kg)	10

Working Temp	105~136°C
Temp. Display Accuracy	0.1°C
Timing range	0~999min
Dynamic Pulse Exhaust Times	0~9 times
Dynamic Pulse Exhaust Temp.	105 ~ 134°C
Consumption	9.5kg
Power Supply	AC110/220V±10%, 50/60Hz
SS Basket	2pcs
Basket Size(mm)	Φ365*260*2pcs
External Size(W*D*H)mm	640*550*1080
Packing Size(W*D*H)mm	750*745*1240
Gross Weight ( kg )	115